



SHOWN ENERGIZED

Model #	Net Pull Force (lbs./newtons)	Net Hold Force (lbs./newtons)	Max. Stroke (inch [mm])	Voltage	Coil Resis. (ohms)	Pull-in (amps)	Hold (amps)	Spring	Boot	Comments & Features
P610-A1V12	15/66.7	23/120	1.00 [25,4]	12 VDC	.25/12	48	1	No	Yes	
P610-A1V24	15/66.7	23/120	1.00 [25,4]	24 VDC	.96/49.5	25	.48	No	Yes	
P610-B1V12	13/57.8	16.5/73.4	1.00 [25,4]	12 VDC	.25/12	48	1	Light	Yes	
P610-B1V24	13/57.8	16.5/73.4	1.00 [25,4]	24 VDC	.96/49.5	25	.48	Light	Yes	
P610-C1V12	12.5/55.6	13.5/60.0	1.00 [25,4]	12 VDC	.25/12	48	1	Heavy	Yes	
P610-C1V24	12.5/55.6	13.5/60.0	1.00 [25,4]	24 VDC	.96/49.5	25	.48	Heavy	Yes	
P610-B7V12	13/57.8	16.5/73.4	1.00 [25,4]	12 VDC	25/12	48	1	Light	Yes	No threaded rod, Packard connector